



A. R. R. - 2000 SERIES - PANAMA FLAT CAR
= SPECIFICATIONS =

*Panama Canal Equipment - (Originally constructed 5 Ft. Gauge,
 Wheels have been Pressed in to Standard 4'-8 1/2" Gauge)*

*Second Hand
 Placed in Service
 Estimated Life
 Lightweight
 Underframe*

- Anchorage 1916-1917
- 16 Years.
- 34500* Approx. Average.
- Wood - B Sills.
- End Sill - 8"x12"x9'-4"
- Intermediate Sill - 5"x9"x39'-0"
- Center Sill - 5"x9"x39'-0"
- Side Sill - 5"x14"x39'-11"

Decking

Pocket for Couplers.

Couplers

Coupler Springs

Follower Plates.

Draw Timbers.

Truss Rods.

Brake Beam

Bolster

- 3"x8"x9'-1"
- 1"x4"x22" Iron - 4"x5"x8 1/2" Space Blocks.
- 5"x7"x8 1/2" "Tower" Undercut.
- 8"x8"
- 1 1/2"x8"x10" & 1 1/2"x8"x7 1/2"
- 4 1/2"x5"x8'-0" Oak.
- Six 1 1/2" Turnbuckle 1 3/4"
- Metal "Monarch"
- Metal "Simplex"

- Truck - Arch Bar - Center to Center - Bearing 6'-7 1/2"
- Center to Center Trucks - 28'-0"
- Wheel Base of Trucks - 5'-4"
- Axles - 5"x9" Journals.
- Wheels - Eight 33" dia. 650*
- Journal Boxes - M.S. Cord Box & Cover.
- Draw Gear - Miners Tandem.
- Air Brakes - New York.

GENERAL DIMENSIONS.

- Train Length - 42'-11"
- Maximum Width - 9'-6"
- Maximum Height - 5'-2"
- Outside Length - 40'-0"
- Height Rail - Platform - 3'-10"

Total Number = ~~325~~

240